# Kubota



**ZG332** 

KUBOTA ZERO-TURN MOWER

Kubota's top-of-the-line Z300 Series offer the highest levels of comfort and performance to exceed even the toughest of commercial demands.

## The new ZG332 mowers deliver unmatched productivity with their powerful liquid-cooled Kubota petrol engine.

- New 32.5HP Kubota 3-cylinder liquid-cooled petrol engine
- · 6.5"-deep, 72"-wide mower deck
- · Semi-pneumatic (flat-free) front caster tyres
- High-performance HST transmission
- Full-flat operator platform
- · High-back deluxe suspension sea
- Adjustable speed control levers
- · Hands-free hydraulic deck lift
- Hands-free parking brake
- Maintenance lift





Kubota's new 32.5HP liquid-cooled petrol engine delivers first-rate levels of torque, productivity, and low engine noise. And like Kubota petrol engines of the past, this new engine has been designed with a proven liquid-cooled Kubota diesel block to assure smooth operations and longevity that only Kubota is known for in this class of engine.

Built to maximize cutting performance, the full-size chassis ZG332 boasts 72-inch Pro Commercial mower deck options to exceed job requirements of turf professionals. Fabricated with a 6.5-inch deep design and unique baffling, Kubota's Pro Commercial decks efficiently generate high suction for a defined cut, while maintaining proper airflow for effective clipping discharge. Additionally, these decks are shaft driven with a hydraulic wet-type PTO clutch, ensuring solid engagement and years of lasting performance.

**Reliable Hydrostatic Transmission** 

As with all 2300 Series, the ZG332 utilizes Kubota's heavy-duty integral twin hydrostatic transmission (HST) for smooth operations. Shaft driven from the engine, this HST features a hydraulic deck-lift valve, wet-type PTO clutch, and nearly 12.3 litre capacity assuring simple, reliable, and cool operations.

\*This information is sourced from overseas and may not necessarily apply locally. It is essential that you confirm specifications and other information with your local Kubota dealer.

### **Specifications**

Model			<b>Z</b> G332
			ZG332LP-72
Engine	Model		Kubota WG972-G-E3-ZG-1
	Type		Petrol, liquid-cooled (3 cyl.)
	Max. horsepower (Gross)		32.5 HP@3600 rpm
	Total displacement		962 cc
	Starting system		Key switch
Dimensions	Overall length		2414 mm
	Overall width	(w/ mower)	2224 mm
		(w/o mower)	1460 mm
	Overall height	(w/ ROPS upright)	1915 mm
		(w/ ROPS folded)	1645 mm
Wheel base			1495 mm
Tread	Front		1070 mm
	Rear		1150 mm
Tyre size	Front		15 x 6.0-6 Non-flat
	Rear		26 x 12.0-12
Weight (w/ mower) (without fuel)			778 kg
Transmission system			2-HST w/ Gear reduction
Speed control			2-hand lever
Travel speed range	Forward		0-17.0 km/h
	Reverse		0-8.5 km/h
Brake type			Wet multi discs, foot applied, released
РТО	Туре		Shaft drive
	Clutch type		Hydraulic independent PTO clutch with wet multi discs
	PTO brake		Wet single disc
Mower deck	Model		RCK72P-332Z
	Mower lift system		Hydraulic
	Mower deck type		Pro commercial – Fabricated deck
	Deck depth		165 mm
	Belt type		Multi-Belt Multi-Belt
	Deck steel thickness		4.6 mm / 4.2 mm
	Anti-scalp roller		Swivel
	Cutting width of mower		72 in.
	Number of blades		3 blades
	Cutting height		1 in. ~ 5 in. / 1/4 in. increments
	Mounting system of mower		Quick joint, parallel linkage
	Blade tip speed (max.)		18200 FPM
Engine stop s			Key stop
Fuel tank capacity			49 ltrs.
Battery			51R (12 Volts, RC: 70 min., CCA: 475A)
Battery			
•	pacity		14 Amps@14 Volts
Battery Alternator cap Fuel gauge	pacity		14 Amps@14 Volts Electric

The company reserves the right to change the above specifications without notice.

This brachure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information.

For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.

For complete operational information, the operator's manual should be consulted.



#### **KUBOTA Tractor Australia Pty Ltd**

25-29 Permas Way, TRUGANINA Vic, 3029 Freecall: 1800 334 653 Email: sales@kubota.com.au

Web Site: http://www.kubota.com.au

#### **CB Norwood Distributors Ltd**

PO Box 1265, 888 Tremaine Avenue, Palmerston North 0800 KUBOTA Tel: 06 356 4920 Fax: 06 356 4939

Web Site: http://www.kubota.co.nz

©2012 Kubota Corporation